

Schaefer Universal System Design Cart

Model USD is for use with standard bar-lock lifters or automated grabbers.



- · Non-slip, textured finish on corners for grabber efficiency
- · Long-lasting, integrated lid hinges
- · Smooth surface inside and out for easy maintenance
- · Injection molded for maximum strength and durability
- One-piece high-density polyethylene (HDPE) construction
- · Built-in flexibility (M Only)



Bar

- · Highly durable, in-molded bar supports
- Freely rotating recycled bar for less stress on cart
- Installed by factory personnel
- · Extra wall thickness in bar area for durability



Upper Attachment

- · Integrated, reinforced upper attachment for semiautomated lifters
- · Structurally designed per ANSI Standards

Handles

- · Ergonomically designed hand grips for ease of pushing/pulling the cart
- · Smooth surface with no protrusions
- · 2" x 5" opening for easy gripping
- · RFID Ready

Wheels & Axles

- · Axle of tempered, rolled, Zink Chromate steel
- · Maintenance-free bearings lubricated for life
- 10" or 12" wheels available for 95M-gallon model
- · 10" wheels on 65-gallon model
- · 8" wheels on 35-gallon model

Bottom

- · In-molded toe hold to ease tilting of loaded cart
- · 0.375" wear strip for longer life

Colors & Marking

- · Available in green, blue, brown and charcoal
- · Custom colors available
- · Smooth surface for hot stamping on lid and body



Lids - USD 95M

- · Overlapping lip for rain protection
- · Inside dripping rim to seal in odors
- · Sturdy, comfortable safe ergonomic handles (2)



Universal System Design Cart (measurements in inches, unless specified)

Order #	Dimensions				Wheel Diameter	Load Rating	Full Truckload
	H	H Cart Body	W	D	5	lbs.▼	
USD 35	38.2	35.8	22.8	22.3	8	125	1008
USD 65	42.2	39.5	25.9	26.5	10	220	660
USD 95M	44.3	41.06	27.6	31.5	10	330	549

ANSI Z245.30 and ANSI Z245.60 Approved ISO 9001 Certified

